

NOTICE OF EMERGENCY MODIFICATION TO 2021 SC BUILDING CODES

At their meeting on November 15, 2022, the S.C. Building Codes Council approved an emergency modification request to delete the below exceptions from the 2021 SC Plumbing Code and 2021 SC Building Code, without substitution.

Approved Modifications:

- Exception 6 was deleted without substitution from Section 403.2 of the 2021 IPC and from Section [P] 2902.2 of the 2021 IBC.
- Exception 2 was deleted without substitution from Section 403.1.1 of the 2021 IPC and from Section [P] 2902.1.1 of the 2021 IBC.

These modifications will take effect on January 1, 2023, and must be enforced by all municipalities and counties in South Carolina.



Applicable Code: 2021 International Building Code Modification Index Number: IBC 2021-19 Code Section: [P] 2902.1.1 Fixture Calculations Modification: Image: Code Section:
 [P] 2902.1.1 Fixture calculations. To determine the <i>occupant load</i> of each sex, the total <i>occupant load</i> shall be divided in half. To determine the required number of fixtures, the fixture ratio or ratios for each fixture type shall be applied to the <i>occupant load</i> of each sex in accordance with Table 2902.1. Fractional numbers resulting from applying the fixture ratios of Table 2902.1 shall be rounded up to the next whole number. For calculations involving multiple occupancies, such fractional numbers for each occupancy shall first be summed and then rounded up to the next whole number. Exceptions: 1. The total <i>occupant load</i> shall not be required to be divided in half where approved statistical data indicates a distribution of the sexes of other than 50 percent of each sex. 2. Where multiple-user facilities are designed to serve all genders, the minimum fixture count shall be eaceulated 100 percent, based on total <i>occupant-load</i>. In such multiple-user user facilities, each fixture type shall be in accordance with ICC A117.1 and each urinal that is provided shall be located in a stall. 3. Distribution of the sexes is not required where single-user water closets and bathing room fixtures are provided in accordance with Section 2902.1.2.

Previous Code Cycles	Previous Modification Index Number	Previous Code Section
N/A		



Applicable Code: 2021 International Plumbing Code
Modification Index Number: IPC 2021-07
Code Section: 403.1.1 Fixture Calculations
Modification:
 403.1.1 Fixture calculations. To determine the occupant load of each sex, the total occupant load shall be divided in half. To determine the required number of fixtures, the fixture ratio or ratios for each fixture type shall be applied to the occupant load of each sex in accordance with Table 403.1. Fractional numbers resulting from applying the fixture ratios of Table 403.1 shall be rounded up to the next whole number. For calculations involving multiple occupancies, such fractional numbers for each occupancy shall first be summed and then rounded up to the next whole number. Exceptions: 1. The total occupant load shall not be required to be divided in half where approved statistical data indicate a distribution of the sexes of other than 50 percent of each sex. 2. Where multiple-user facilities are designed to serve all genders, the minimum fixture count
 shall be calculated 100 percent, based on total occupant load. In such multiple-user facilities, each fixture type shall be in accordance with ICC A117.1 and each urinal that is provided shall be located in a stall. 3. Distribution of the sexes is not required where single-user water closets and bathing room fixtures are provided in accordance with Section 403.1.2.

Previous Code Cycles	Previous Modification Index Number	Previous Code Section
N/A		



Applicable Code: 2021 International Building Code			
Modification Index Number: IBC 2021-20			
Code Section: [P] 2902.2 Separate facilities			
Modification:			
[P] 2902.2 Separate facilities. Where plumbing fixtures are			
required, separate facilities shall be provided for each sex.			
Exceptions:			
1. Separate facilities shall not be required for <i>dwelling</i>			
units and sleeping units.			
2. Separate facilities shall not be required in structures			
or tenant spaces with a total occupant load,			
including both employees and customers, of 15 or fewer.			
3. Separate facilities shall not be required in mercantile			
occupancies in which the maximum occupant			
load is 100 or fewer.			
4. Separate facilities shall not be required in business			
occupancies in which the maximum occupant			
load is 25 or fewer.			
5. Separate facilities shall not be required to be			
designated by sex where single-user toilets rooms			
are provided in accordance with Section 2902.1.2.			
6. Separate facilities shall not be required where			
rooms having both water closets and lavatory			
fixtures are designed for use by both sexes and			
privacy for water closets are installed in accordance			
with Section 405.3.4 of the International			
Plumbing Code. Urinals shall be located in an area			
visually separated from the remainder of the facility			
or each urinal that is provided shall be located in a stall.			

Previous Code Cycles	Previous Modification Index Number	Previous Code Section
N/A		



Applicable Code: 2021 International Plumbing Code			
Modification Index Number: IPC 2021-08			
Code Section: 403.2 Separate facilities			
Modification:			
 403.2 Separate facilities. Where plumbing fixtures are required, separate facilities shall be provided for each sex. Exceptions: Separate facilities shall not be required for dwelling units and sleeping units. Separate facilities shall not be required in structures or tenant spaces with a total occupant load, including both employees and customers, of 15 or fewer. Separate facilities shall not be required in mercantile <i>occupancies</i> in which the maximum occupant load is 100 or fewer. Separate facilities shall not be required in business <i>occupancies</i> in which the maximum occupant load is 25 or fewer. Separate facilities shall not be required to be designated facilities shall not be required to be designated by sex where single-user toilet rooms are provided in accordance with Section 403.1.2. Separate facilities shall not be required where rooms having both water closets and lavatory fixtures are designed for use by both sexes and privacy for water closets is provided in accordance with Section 405.3.4. Urinals shall be located in an area visually separated from the remainder of the facility or each urinal that is provided shall be located in a stall. 			

Previous Code Cycles	Previous Modification Index Number	Previous Code Section
N/A		